Technical data Access Pro-H

Lane width max.	6.0 m	
Opening / closing time	4.0 s	
Power consumption max.	25 W	
Duty cycle	100%	
Supply voltage	Wide voltage range 85 - 264 V AC (also available as 24V DC version)	
Frequency	50 - 60 Hz	
Housing dimensions (W x D x H)	315 x 360 x 1115 mm	
Drive system	MHTM™ MicroDrive	
Weight (without boom)	44 kg	
Housing design	Powder-coated aluminium	
Base frame	Powder-coated stainless steel	
Protection class	IP 54	
Compliant with	2004/108/EG, 2006/42/EG, 305/2011, CE, UL 325	
Temperature range	-30 to +55 ℃	

Features Access Pro-H

Standard colour	3 variants	
Special painting	0	
Barrier boom	MicroBoom	
Boom skirt / over-climb protection	0/0	
Control unit	MGC Pro	
Integrated 2-channel loop detector	•	
Control unit modularly extendable	•	
Variable I/O assignment	•	
Number of digital inputs	8	
Anzahl Relais-/digital outputs	6/4	
Closing times selectable	•	
Opening times selectable	•	
Solar / battery option	0	
Extended accessories	0	
Specified number of cycles	10 Mio	
Warranty	2 years	

StandardOptionally availabe

Technical data A	Access XL	Access XXL
------------------	-----------	------------

Lane width max.	8.5 m	10.0 m
Opening / closing time	6.0 s	8.0 s
Power consumption max.	17 W	30 W
Duty cycle	100%	
Supply voltage	Wide voltage range 85 - 264 V AC (also available as 24V DC version)	
Frequency	50 - 60 Hz	
Drive system	MHTM™ MicroDrive	
Housing dimensions (W x D x H)	315 x 360 x 1169 mm	435 x 360 x 1169 mm
Weight (without boom)	93 kg	112 kg
	Powder-coated aluminium	
Housing design	Powder-coate	ed aluminium
Housing design Inner support frame	Powder-coate Surface zinc phospate plu	
		s cathodic electrophoresis
Inner support frame	Surface zinc phospate plu	s cathodic electrophoresis

Features Access XL Access XXL

Standard colour	RAL 2000	RAL 2000
Special painting	0	0
Barrier boom	MicroBoom XL	MicroBoom XL
Control unit	MGC Pro	MGC Pro
Integrated 2-channel loop detector	•	•
Control unit modularly extendable	•	•
Variable I/O assignment	•	•
Number of digital inputs	8	8
Number of relay / digital outputs	6/4	6/4
Safety light barrier input with test	•	•
Opening / closing times selectable	•/•	•/•
Extended accessories (e.g. boom skirt)	0	0
Warranty	2 years	2 years

- Standard
- \circ
- Optionally available Not available for this model