

Technical data	Magnetic.Toll	Magnetic.Toll Pro	Magnetic.Toll HighSpeed
Lane width max.	3.0 m	3.0 m	3.0 m
Opening / closing time	1.3 s	0.9 s	0.6 s
Power consumption max.	55 W	95 W	320 W
Duty cycle	100%		
Supply voltage	Wide voltage range 85 - 264 V AC		
Frequency	50 - 60 Hz		
Drive system	MHTM™ MicroDrive		
Housing dimensions (W x D x H)	315 x 360 x 1115 mm		
Weight (without boom)	42 kg		
Housing design	Powder-coated aluminium		
Base frame	Powder-coated stainless steel		
Protection class	IP 54		
Compliant with	2004/108/EG, 2006/42/EG, 305/2011, CE, UL 325	CE, 2006/42/EG, 2004/108/EG	
Temperature range	-30 to +55 °C		

Features	Magnetic.Toll	Magnetic.Toll Pro	Magnetic.Toll HighSpeed
Standard colour	RAL 2000	RAL 2000	RAL 2000
Special painting	○	○	○
Control unit	MGC	MGC	MGC
MGC Pro Control unit	○	○	○
Control unit modularly extendable	●	●	●
MicroBoom-T (Ø 75 mm)	●	●	●
MicroBoom-S (100 x 55 mm)	○	○	○
MicroBoom AT	○	○	○
Swing-Away Flansch	●	●	●
Auto-Swing-Away Flansch	○	○	○
Number of digital inputs	8	8	8
Number of relay / digital outputs	6/4	6/4	6/4
Closing times selectable	●	●	●
Extended accessories	○	○	○
Specified number of cycles	10 Mio	10 Mio	10 Mio
Warranty	2 years	2 years	2 years

- Standard
- Optionally available